

## **Annex to Resolution 3 (2006)**

# **Practical Guidelines for Ballast Water Exchange in the Antarctic Treaty Area**

1. The application of these Guidelines should apply to those vessels covered by Article 3 of the IMO's International Convention for the Control and Management of Ships' Ballast Water and Sediments (the Ballast Water Management Convention), taking into account the exceptions in Regulation A-3 of the Convention. These Guidelines do not replace the requirements of the Ballast Water Management Convention, but provide an interim Ballast Water Regional Management Plan for Antarctica under Article 13 (3).
2. If the safety of the ship is in any way jeopardised by a ballast exchange, it should not take place. Additionally these guidelines do not apply to the uptake or discharge of ballast water and sediments for ensuring the safety of the ship in emergency situations or saving life at sea in Antarctic waters.
3. A Ballast Water Management Plan should be prepared for each vessel with ballast tanks entering Antarctic waters, specifically taking into account the problems of ballast water exchange in cold environments and in Antarctic conditions.
4. Each vessel entering Antarctic waters should keep a record of ballast water operations.
5. For vessels needing to discharge ballast water within the Antarctic Treaty area, ballast water should first be exchanged before arrival in Antarctic waters (preferably north of either the Antarctic Polar Frontal Zone or 60°S, whichever is the furthest north) and at least 200 nautical miles from the nearest land in water at least 200 metres deep (If this is not possible for operational reasons then such exchange should be undertaken in waters at least 50 nautical miles from the nearest land in waters of at least 200 metres depth).
6. Only those tanks that will be discharged in Antarctic waters would need to undergo ballast water exchange following the procedure in Paragraph 5. Ballast Water Exchange of all tanks is encouraged for all vessels that have the potential/capacity to load cargo in Antarctica, as changes in routes and planned activities are frequent during Antarctic voyages due to changing meteorological and sea conditions.
7. If a vessel has taken on ballast water in Antarctic waters and is intending to discharge ballast water in Arctic, sub-Arctic, or sub-Antarctic waters, it is recommended that ballast water should be exchanged north of the Antarctic Polar Frontal Zone, and at least 200 nautical miles from the nearest land in water at least 200 metres deep. (If this is not possible for operational reasons then such exchange should be undertaken in waters at least 50 nautical miles from the nearest land in waters of at least 200 metres depth).
8. Release of sediments during the cleaning of ballast tanks should not take place in Antarctic waters.
9. For vessels that have spent significant time in the Arctic, ballast water sediment should preferably be discharged and tanks cleaned before entering Antarctic waters (south of 60°S). If this cannot be done then sediment accumulation in ballast tanks should be monitored and sediment should be disposed of in accordance with the ship's Ballast Water Management Plan. If sediments are disposed of at sea, then they should be disposed of in waters at least 200 nautical miles from the shoreline in waters at least 200 metres deep.
10. Treaty Parties are invited to exchange information (via the Council of Managers of National Antarctic Programs) on invasive marine species or anything that will change the perceived risk associated with ballast waters.